

**DS-K1108A  
Card Reader**

114-124B



- 32-bit high-speed processor
- Support RS-485, Wiegand (W26, W34) protocol, and OSDP protocol
- Supports reading EM card (Frequency: 125 KHz) (DS-K1108AE/DS-K1108AEK)
- Supports reading Mifare card (Frequency: 13.56 MHz). Meets the standard of ISO 14443-A (DS-K1108AM/DS-K1108AMK)
- Supports reading Mifare card, Desfire card, and Felica card (DS-K1108AD/DS-K1108ADK)
- Tamper-proof function
- Built-in buzzer for status indication
- Online upgrading
- Accurate data and time display provided by built-in electronic clock and watchdog program to ensure the basic function of the terminal

## ▪ Specification

<b>System</b>	
Processor	32 bit
<b>Audio</b>	
Audio alert	Beeper
<b>Network</b>	
Communication protocol	RS-485/Wiegand (Set via DIP switch)
<b>Authentication</b>	
Card reading distance	≤ 50 mm (1.97")
Card radio frequency standard	ISO 14443-A
<b>Function</b>	
ID settings	via DIP switch
<b>Others</b>	
Keypad	DS-K1108AE/DS-K1108AM/DS-K1108AD: No keypad DS-K1108AEK/DS-K1108AMK/DS-K1108ADK: With keypad
Indicator	Power indicator; Status LED indicator
Power supply	12 VDC, 2 W
Working temperature	-20°C to 65°C (-4°F to 149°F)
Working humidity	10% to 90% (Non condensing)
Dimensions	123 mm × 88 mm × 21mm (4.84" × 3.46" × 0.83")
Protective level	IP65
Installation	Wall mounting
Approval	FCC, CE

## ORDERING INFORMATION

114-124B

Hikvision DS-K1108AM Card Reader



Innovative Electronic Solutions  
www.ness.com.au



**NSW** Ph 02 8825 9222  
sales@ness.com.au

**VIC** Ph 03 9875 6400  
nessmelb@ness.com.au

**QLD** Ph 07 3399 4910  
nessbris@ness.com.au

**WA** Ph 08 9328 2511  
nessper@ness.com.au

**SA** Ph 08 8152 0000  
adelaide@ness.com.au